

QUALITY CONTROL LABORATORY

Certificate of analysis

page 1 of 1

Certificate of Analysisnumber	LS-24-1126	Product Code	Miller Oils
Sample Recieved Date:	8/29/2024		
Product Name	Trident Professional 5W-30 504/507	Batch Number	1942376818
		Date of Test	8/29/2024
CHARACTERISTICS			
Test	Method	Units	Result
Appearance	Visual	-	Bright & Clear
Color	ASTM D1500	-	L-3.0
Kinematic viscosity at 100 °C	ASTM D445	cSt	11.94
Kinematic viscosity at 40 °C	ASTM D445	cSt	71.7
Density at 15 °C	ASTM D4052	g/ml	0.8501
Viscosity index	ASTM D2270	-	163
Low Temperature Cranking	ASTM D5293	mPa.S	5714
Viscosity at -30C			
Noack	ASTM D5800	% mass	7.6
Flash Point (COC)	ASTM D92	°C	238
Pour Point	ASTM D97	°C	-42
Base Number	ASTM D2896	mg KOH/g	8.67
Sulfur	ASTM 5354	% mass	0.265
Nitrogen	ASTM D5762	% mass	0.13
Sulphated Ash	ASTM D874	% mass	0.76401
Calcium	ASTM D5185	% mass	0.135
Magnesium	ASTM D5185	% mass	0.033
Phosphorus	ASTM D5185	% mass	0.076
Zinc	ASTM D5185	% mass	0.088
Boron	ASTM D5185	% mass	0.003
Moly	ASTM D5185	% mass	0
HTHS	ASTM D4683	cP	4.22
SSI 30cycle	ASTM D6278	cSt	11.13
Foaming Tendency			
Sequence I Tend/Stab	ASTM D892	ml/ml	5/0
Sequence II Tend/Stab	ASTM D892	ml/ml	20/0
Sequence III Tend/Stab	ASTM D892	ml/ml	5/0

Issued By: Lab Chemist

Date: 8/29/2024