

QUALITY CONTROL LABORATORY

Certificate of analysis

page 1 of 1

Certificate of Analysisnumber	LS-24-1412		Product Source	COMMA
Sample Recieved Date:	14/10/2024			
Product Name	COMMA X-Flow ACEA A5/B5, API SL/CF TYPE F 5W-30	Batch/Serial Number	122024.05.25/32 4949	
		Date of Test	18/10/2024	
CHARACTERISTICS				
Test	Method	Units	Result	
Appearance	Visual	-	Bright & Clear	
Color	ASTM D1500	-	L3.0	
Kinematic viscosity at 100 °C	ASTM D445	cSt	10.42	
Kinematic viscosity at 40 °C	ASTM D445	cSt	62.43	
Density at 15 °C	ASTM D4052	g/ml	0.8536	
Viscosity index	ASTM D2270	-	156	
Low Temperature Cranking	ASTM D5293	mPa.S	5591	
Viscosity at -30C				
Noack	ASTM D5800	% mass	6.2	
Flash Point (COC)	ASTM D92	°C	234	
Pour Point	ASTM D97	°C	-36	
Base Number	ASTM D2896	mg KOH/g	10.79	
Sulfur	ASTM 5354	% mass	0.299	
Nitrogen	ASTM D5762	% mass	0.09	
Sulphated Ash	ASTM D874	% mass	1.278	
Calcium	ASTM D5185	% mass	0.323	
Magnesium	ASTM D5185	% mass	0	
Phosphorus	ASTM D5185	% mass	0.104	
Zinc	ASTM D5185	% mass	0.12	
Boron	ASTM D5185	% mass	0	
Moly	ASTM D5185	% mass	0.01	
HTHS	ASTM D4683	cP	3.34	
SSI 30cycle	ASTM D6278	cSt	9.53	
Foaming Tendency				
Sequence I Tend/Stab	ASTM D892	ml/ml	10/0	
Sequence II Tend/Stab	ASTM D892	ml/ml	30/0	
Sequence III Tend/Stab	ASTM D892	ml/ml	10/0	

Issued By: Lab Chemist

Date: 18/10/2024